

**TS 420 STIHL Cutquik®****TS 420 Cutquik®****Series 4238****Professional Use**

The TS 420 STIHL Cutquik® cut-off machine — one of the best we've ever built. Helping you work longer and more comfortably, this cut-off machine comes with a 14" wheel, delivering a unique blend of performance and efficiency so you get the job done right. With the revolutionary X2 air filtration system, an anti-vibration system, and a lightweight design, you get low maintenance and more maneuverability. Its advanced engine technology also increases fuel efficiency and reduces emissions.

*(Abrasive wheel included. Diamond wheel (shown) is sold separately.)*

**Standard Features**

- X2 low-maintenance air filtration system
- Anti-vibration system reduces vibration up to 43% over previous models
- Powerful and fuel-efficient, low-emission engine
- Emissions reduced up to 44% compared to previous models
- Lightweight and well balanced compact top handle design
- Semi-automatic belt tensioner
- Reversible cutting arm for inboard or outboard cutting

**Optional Features**

- TS Rental Kit
- Leather Chaps
- Portable Water Tank
- Metal TS Case
- Roller Wheel Kit
- Mounting Kit and Cart

**IMPORTANT INFORMATION**

**WARNING!** Never use carbide-tipped, wood cutting or circular saw blades on cut-off machines. They can cause severe personal injury or death from reactive forces, blade contact or thrown tips. Never cut wood of any type.

**Note:** STIHL recommends use of fuel with no more than 10% Ethanol content. Using fuel with greater than 10% Ethanol content may cause damage to your equipment and may void your STIHL warranty. [Learn More...](#)

**Note:** STIHL engine products with the Caring for Nature logo are cleaner than EPA Standards for exhaust emissions.

**WARNING!** Improper use of any power tool may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your instruction manual before using such products.

**STIHL products sold through U.S. STIHL dealers are for distribution in the United States only.**

**Specifications**

DISPLACEMENT	66.7 cc (4.07 cu. in.)
ENGINE POWER	3.2 kW (4.4 bhp)
WEIGHT*	9.6 kg (21.2 lbs.)
FUEL TANK CAPACITY	710 cc (24 oz.)
ENGINE SPEED	9,000 rpm (Elec. Gov.)
MAX SPINDLE SPEED	5,350 rpm
ARBOR SIZE	20 mm
MAXIMUM WHEEL SIZE	350 mm (14")
MAXIMUM CUTTING DEPTH	125 mm (4.9")

\*Weight includes water attachment and guard.