



2016 PIONEER 700-4 SPECIFICATIONS*

ENGINE	
Engine Type	675cc liquid-cooled OHV single-cylinder four-stroke
Bore And Stroke	102.0mm x 82.6mm
Compression Ratio	9.2:1
Induction	Fuel Injection (PGM-FI), 40mm throttle body
Ignition	Full-transistorized with electronic advance
DRIVE TRAIN	
Clutch	Automatic
Transmission	Automotive-style with hydraulic torque converter, three forward gears and Reverse. Three drive modes include 2WD, 4WD and 4WD with differential lock
Driveline	Direct front and rear driveshafts
CHASSIS / SUSPENSION / BRAKES	
Front Suspension	Independent double-wishbone; 7.9 inches travel
Rear Suspension	Independent double-wishbone; 9.1 inches travel
Front Brake	200mm hydraulic disc
Rear Brake	170mm hydraulic disc
Front Tires	25 x 8-12
Rear Tires	25 x 10-12
DIMENSIONS	
Length	114.8 inches
Width	60.0 inches
Height	78.3 inches
Wheelbase	76.8 inches
Bed Capacity	1000 pounds
Towing Capacity	1500 pounds
Ground Clearance	10.5 inches
Turning Radius	14.8 feet
Curb Weight	1396 pounds
Fuel Capacity	8.2 gallons, including 1.2-gallon reserve
OTHER	
Note	Recommended for Drivers 16 years of age and older.
Available Colors	Red, Metallic Silver, Honda Phantom Camo®
Model Id	SXS700M4
FACTORY WARRANTY INFORMATION	
Duration	One Year
Description	Transferable limited warranty; extended coverage available with a Honda Protection Plan