

## SMALL REPAIR JOBS JUST GOT EASIER!

### C914P COMPACT PUSH SAW

With extreme reliability, portability, and strong performance, the new full featured Norton Clipper C914P walk-behind saw is redefining the compact concrete saw class.

The powerful Honda 9HP engine, 14" maximum blade capacity, and the strongest chassis in class make for the fastest and straightest cuts every time. Designed for easy transportation, simple operation, and low maintenance, the C914P is the right choice for contractors and rental. The C914P is equally at home cutting concrete, sidewalks, asphalt, or decorative concrete making it the perfect saw for any job.

**KEY APPLICATIONS**  
EXPANSION JOINT CLEANING  
GREEN CONCRETE CUTTING  
PATCH WORK REPAIRS  
JOINT CUTTING | DEMOLITION

**REDEFINING  
JOBSITE MUSCLE™**



C914P SAW FEATURES



**Adjustable Height Handle Bars**  
Stay-level handle bar system adjusts to four different positions for the utmost in operator comfort.



**Quick Belt Tensioning**  
Easy to change V belts for fast and accurate belt tensioning.



**Water Supply**  
Includes a water tank with garden hose fitting.

Technical Specifications

DESCRIPTION	C914P
<b>Product Number</b>	701846 <b>08504</b>
Blade Guard Capacity - in. (mm)	14 (350)
Maximum Depth of Cut - in. (mm)	4.3 (110)
Arbor Size - in. (mm)	1 (25.4)
Blade Flange Diameter - in. (mm)	4 (107)
Blade Shaft RPM	2,840
Blade Shaft Diameter - in. (mm)	0.866 (22)
Blade Shaft Bearings	Heavy Duty Pillow Block
Blade Shaft Drive	3 Belts
Blade Guard Attachment	Hinged, All Steel
Blade Control	Hand Wheel/Screw Feed
Axle - Front - in (mm)	0.59 (15)
Axle - Rear - in (mm)	0.78 (20)
Wheels - Front - in (mm) D x W x B	3.93 x 1.38 x 0.59 (100 x 35 x 15)
Wheels - Rear - in (mm) D x W x B	7.87 x 1.77 x 0.79 (200 x 45 x 20)
Handle Bars/Adjustment Length	9.45 (245)
Control	Push
Chassis	Heavy Duty Box Design
Water Tank Capacity - gal (l)	6.6 (25)
Power Source	Gasoline, Single Cylinder 4 Cycle
Motor/Engine Type	Honda
Maximum Horsepower* (kW)	9 (6.7)
Net Horse Power* (kW)	6.5 (4.8)
Displacement - cu In (l)	16.5 (0.27)
Bore - in (mm)	3.0 (77)
Stroke - in (mm)	2.3 (58)
Cylinders/Cycle	Single Cylinder 4 Cycle
Fuel Capacity - gal (l)	1.4 (5.3)
Oil Capacity - qt (l)	0.29 (1.1)
Airfilter	Four Stage Cyclone
Starter	Manual
Engine Cooling	Forced Air
<b>Saw Dimensions</b>	
Height - in (mm)	37.92 (963)
Minimum Saw Length (Transport) - in (mm)	35.57 (929)
Maximum Saw Length (Working) - in (mm)	57.85 (1,469)
Maximum Pointer Length - in (mm)	21.28 (541)
Frame Width - in (mm)	12.73 (323)
Saw Width - in (mm)	19 (483)
Front (Outside to Outside Wheel Width) - in (mm)	12.73 (323)
Rear (Outside to Outside Wheel Width) - in (mm)	13.70 (348)
Blade to Wall - in (mm)	1.38 (35)
Wheel Base Length - in (mm)	17.32 (440)
Weight Crated - lbs. (kg)	198.4 (90.6)
Weight - Uncrated - lbs (kg)	169.4 (77)

\* = Data Provided by Engine Manufacturer

**REDEFINING  
JOBSITE MUSCLE™**

www.facebook.com/**NortonAbrasivesNA** | www.youtube.com/**NortonAbrasives** | www.nortonabrasives.com

**USA CUSTOMER SERVICE:**

Toll Free Phone: 1 (800) 554-8003  
Toll Free Fax: 1 (800) 443-1092

**CANADA CUSTOMER SERVICE:**

Toll Free Phone: 1 (800) 263-6565  
Toll Free Fax: 1 (800) 561-9490

**FORM #8818** REV. 01/22

© Saint-Gobain January 2022.

Norton, Norton Clipper, "Redefining Jobsite Muscle" and "Transforming surfaces...and beyond" are trademarks of Saint-Gobain Abrasives. All other trademarks are the property of their respective owners.

